

J40

HIGHLY PORTABLE JAW CRUSHER

The J40 Jaw Crusher continues McCloskey's focus on quality, durability, and productivity. With heavy duty cheekplate design, 40" wide jaw and user-friendly control panel with excellent machine diagnostics, the J40 provides contractors with a highly portable option while meeting all production expectations. At 2.5 metres wide, it's ideal for applications that require a high degree of mobility.

Maximum productivity is delivered through the enhancements to the deeper jaw box, including a faster jaw speed and a larger gap between the crusher discharge and main conveyor feedboot.

The J40 retains the core values expected in a full size McCloskey Jaw Crusher, including high capacity production and heavy duty build, packaged for efficiency and mobility.



CONTROL PANEL

User friendly waterproof and dustproof control panel. Allows monitoring of pressures, fluid levels and fuel consumption. Provides push button control of jaw, track and feeder functions.



MAIN CONVEYOR

36" main conveyor as standard, giving large stockpile capacity. Conveyor lowers and raises hydraulically.

JAW CRUSHER

True 40" x 24" jaw with reversible hydrostatic drive, reversible jaw plates, and fully hydraulic closed side setting (CSS) adjust.



FEEDER

Folding Hardox® hopper mounted over vibrating pan feeder built with steeper angles to reduce material sticking. Feeder rate regulated manually or automatically by load sensing jaw.

OPTIONAL MAGNET

Optional overband magnet enables magnetic material separation from the source material.



IDEAL TRANSPORT SIZE

At only 2.5 m wide, the J40 is easily transported between job sites.

Engine	225 hp (166 kW) Diesel
Transport Height	10' 6" (3.20m)
Transport Length	45' 2.6" (13.78m)
Transport Width	8' 2.5" (2.50m)
Weight-w/ magnet & side conveyor	76,280 lb (34,600kg)
Crushing Chamber	40"(wide) x 24"(pitman opening)
Stockpile Height - Main Conveyor	11' 4.2" (3.47m)
Stockpile Height - Side Conveyor	8' 2" (2.50m)